



Belső méret
760x520x600 mm

Platform méret
730x455 mm

Külső méret
1140x930x1060
mm

185 literes kapacitás



MotorClean
BY TIERRATECH

MOT-185 ADVANCED

EN

ig b rmi

Ultragangos tisztító tartály 2 mm-es AISI 304-es rozsdamentes acélból, 20 mm-es hő akusztikus szigeteléssel

Tartály kapacitás: 185 liter
WFS kapacitás: 30 liter
Teljes kapacitás: 215 liter

Tartály fedele polipropilénből, 4 mm-es dupla fallal és 20 mm-es hő akusztikus szigeteléssel

Pneumatikus platform AISI 304 rozsdamentes acélból készült, teherbíró képessége 60 kg, állítható fel- le mozgatóval

WFS (Waterflow system for oil separation), auxiliary tank for the collection of oils and particles floating on the surface of the main cleaning tank, with minimum water level detector and drain for the oil outlet and maintenance. Capacity 30 litres

Electrical resistor made of stainless steel AISI 316L, with a power of 3500W

Filter bag TTF1 (optional) for removal of sludge from the bottom of the tank built in AISI 304 stainless steel, manometer and the possibility of integrating bags of 5 to 200 microns.

Generator és Emitter

Ultrasonic generator, output power of 1800W (3600W p-p) with automatic power and frequency wave monitoring. Working frequency 40 KHZ, Sweep System $\pm 2\%$.

1800W ultrasonic emitters (3600W p-p) of power built in stainless steel AISI 316 L, 2.5 mm thick with 36 high-performance titanium-steel IBL piezoelectric transducers with 50W each.

Control Panel

7" Screen & TFT Display

Time control for equipment preheating, weekly calendar, alarms, US direct selectors, heating resistance, platform lift and lowering, continues vertical motion up and down system and water level control.

Conformity Assessment according to Annex I to directive 2006/42/EC

TÜVRheinland[®]
Documento N°.: EC/105/17

Lubkontakt Kft.

www.lubkontakt.hu



www.tierratech.com